

*

COMMUNICATION

E 17 55R - 020018 Concerning:

APPROVAL GRANTED APPROVAL EXTENDED APPROVAL REFUSED APPROVAL WITHDRAWN PRODUCTION DEFINITELY DISCONTINUED

of a type of mechanical coupling device or component pursuant to Regulation No. 55

APPROVAL No. E17*55R02/00*0018*01

1.	Trade name or mark of the device or component:	TAV50-v2, TAV50SR-v2
2.	Type of device or component:	TAV50-v2 Versions: TAV50-v2 or TAV50SR-v2
3.	Manufacturer's name and address:	M. Korte Oy Menotie 2 FI-33470 Ylöjärvi FINLAND
4.	If applicable, name and address of the manufacturer's representative:	n.a.
5.	Alternative supplier's names or trademarks applied to the device or component:	n.a.
6.	Name and address of company or body taking responsibility for the conformity	
	of production:	See item 3.
7.	Submitted for approval on:	29.01.2021, 27.05.2024
8.	Technical Service responsible for conducting approval tests:	Oy Testmill Ltd Hansatie 3 FI-13430 Hämeenlinna FINLAND
9.	Brief description:	anoita San San San San San San San San San Sa
9.1.	Type and class of device or component:	C50-X; Non-standard drawbar coupling

Finnish Transport and Communications Agency Traficom • PO Box 320, 00059 TRAFICOM • Tel. +358 29 534 5000 • Business ID 2924753-3 www.traficom.fi



ransport and Communications Agency Characteristic values:	Date 11.06.2024	2(5) Index number TRAFICOM/296653/05.03.42/2024
Primary values:	D Dc S U V	220 kN n.a. kN n.a. kg n.a. tonnes n.a. kN
Alternative values:	D Dc S U V	- kN - kN - kg - tonnes - kN

manufacturer:

9.2.

9.2.1.

9.3. For Class A mechanical coupling devices or components, including towing brackets:

	1 8	1 ,
	Maximum permissible vehicle mass as declared by the vehicle manufacturer's:	n.a.
	Distribution of maximum permissible vehicle mass between the axles:	n.a.
	Vehicle manufacturer's maximum permissible towable trailer mass:	n.a.
	Vehicle manufacturer's maximum permissible static mass on coupling ball:	n.a.
	Maximum mass:	
	Maximum mass of the vehicle, with bodywork, in running order, including coolant, oils, fuel, tools and spare wheel (if supplied) but not including driver:	n.a.
	Loading condition under which the tow ball height of a mechanical coupling device fitted to category M_1 vehicles is to be measured - see paragraph 2. of Appendix 1, Annex 7:	n.a.
9.4.	For Class B coupling heads, is the coupling head intended to be fitted to an unbraked O_1 trailer:	Yes / No
10.	Instructions for the attachment of the coupling device or component type to the vehicle and photographs or drawings of the mounting points (see Annex 2, Appendix 1) given by the vehicle	See attachment 6

See attachment 6 of the manufacturer sinformation document *



Index number

Finnish Transport and Communications Agency		11.06.2024	TRAFICOM/296653/05.03.42/2024		
11.	Information on the fitting of any special reinforcing brackets or plates or spacing components necessary for the attachment of the coupling device or component (see Annex 2, Appendix 1):				
12.	Additional information where the use of the coupling device or component is restricted to special types of vehicles - see Annex 5, paragraph 3.4.	n.a.			
13.	For Class K hook type couplings, details of the drawbar eyes suitable for use with the particular hook type:				
14.	Date of test report:	19.02.202	1, 23.05.2024		
15.	Number of test report:	TM*T196	*R55*00121, TM*T196*R55*00324		
16.	Approval mark position:		o side of the jaw, see test report *R55*00121		
17.	Reason(s) for extension of approval:	- Me co	odifications to components of the upling device		
18.	Approval granted / refused / extended / withdrawn				
19.	Place	Helsinki			
20.	Date	11.06.202	4		

Date

21. Signature

Mantes Fil

Marko Sinerkari Chief, Type Approval

- 22. The list of documents deposited with the Type Approval Authority which has granted approval is annexed to this communication and may be obtained on request:
 - Manufacturer's information document TAV50-v2 with new and updated attachments, 03.05.2024, 12 pages
 - Test report TM*T196*R55*00324, 23.05.2024, 8 pages

Total number of pages: 20

