


COMMUNICATION



Concerning:

~~APPROVAL GRANTED~~  
~~APPROVAL EXTENDED~~  
~~APPROVAL REFUSED~~  
~~APPROVAL WITHDRAWN~~  
~~PRODUCTION DEFINITELY DISCONTINUED~~

of a type of mechanical coupling device or component pursuant to Regulation No. 55

**APPROVAL No. E17\*55R02/00\*0018\*02**

- E17\*55R02/00\*0018\*02
- |      |   |  |
|------|---|--|
| 1.   | Trade name or mark of the device or component:  | TAV50-v2, TAV50SR-v2   |
| 2.   | Type of device or component:  | TAV50-v2<br>Versions: TAV50-v2 or TAV50SR-v2                       |
| 3.   | Manufacturer's name and address:  | <i>TAV Finland Oy</i><br>Menotie 2<br>FI-33470 Ylöjärvi<br>FINLAND |
| 4.   | If applicable, name and address of the manufacturer's representative:                       | n.a.   |
| 5.   | Alternative supplier's names or trademarks applied to the device or component:              | n.a.   |
| 6.   | Name and address of company or body taking responsibility for the conformity of production: | See item 3.  |
| 7.   | Submitted for approval on:  | 29.01.2021, 27.05.2024, 19.12.2025                                 |
| 8.   | Technical Service responsible for conducting approval tests:                                | Oy Testmill Ltd<br>Hansatie 3<br>FI-13430 Hämeenlinna<br>FINLAND   |
| 9.   | Brief description:  |  |
| 9.1. | Type and class of device or component:  | C50-X; Non-standard drawbar coupling                               |



9.2. Characteristic values:

9.2.1. Primary values:

D	220 kN
D <sub>c</sub>	n.a. kN
S	n.a. kg
U	n.a. tonnes
V	n.a. kN

Alternative values:

D	- kN
D <sub>c</sub>	- kN
S	- kg
U	- tonnes
V	- kN

9.3. For Class A mechanical coupling devices or components, including towing brackets:

Maximum permissible vehicle mass as declared by the vehicle manufacturer's: n.a.

Distribution of maximum permissible vehicle mass between the axles: n.a.

Vehicle manufacturer's maximum permissible towable trailer mass: n.a.

Vehicle manufacturer's maximum permissible static mass on coupling ball: n.a.

Maximum mass:

Maximum mass of the vehicle, with bodywork, in running order, including coolant, oils, fuel, tools and spare wheel (if supplied) but not including driver: n.a.

Loading condition under which the tow ball height of a mechanical coupling device fitted to category M<sub>1</sub> vehicles is to be measured - see paragraph 2. of Appendix 1, Annex 7: n.a.

9.4. For Class B coupling heads, is the coupling head intended to be fitted to an unbraked O<sub>1</sub> trailer: Yes / No

10. Instructions for the attachment of the coupling device or component type to the vehicle and photographs or drawings of the mounting points (see Annex 2, Appendix 1) given by the vehicle manufacturer:

See attachment 6 of the manufacturer's information document (*annexed to extension*)



E17\*55R02/00\*0018\*02

11. Information on the fitting of any special reinforcing brackets or plates or spacing components necessary for the attachment of the coupling device or component (see Annex 2, Appendix 1): n.a.
12. Additional information where the use of the coupling device or component is restricted to special types of vehicles - see Annex 5, paragraph 3.4. n.a.
13. For Class K hook type couplings, details of the drawbar eyes suitable for use with the particular hook type: n.a.
14. Date of test report: 19.02.2021, 23.05.2024
15. Number of test report: TM\*T196\*R55\*00121, TM\*T196\*R55\*00324
16. Approval mark position: On the top side of the jaw, see test report TM\*T196\*R55\*00121
17. Reason(s) for extension of approval: | - *Manufacturer's name changed*
18. Approval ~~granted~~ / ~~refused~~ / extended / ~~withdrawn~~
19. Place Helsinki
20. Date 07.01.2026
21. Signature

*Marko Sinerkari*

Marko Sinerkari  
Head of Department, Vehicle Approval

22. The list of documents deposited with the Type Approval Authority which has granted approval is annexed to this communication and may be obtained on request:

- Manufacturer's information document TAV50-v2 with updated attachments, 19.12.2025, 4 pages

Total number of pages: 4



E17\*55R02/00\*0018\*02